IHSM12R011T2

V_{DSS}	1200 V
$R_{DS(on)}$	11 mΩ

HAWKPACK PF2 series

1200 V, 11 mΩ, Silicon Carbide, T-type three-level Module



Press-fit low-profile, large

Features

- Three-level T-type phase leg in one module
- Lower switching loss than two-level at high DC-link voltage
- Baseplate-less, press-fit pins

Typical applications

- Three-level solar and storage inverters
- UPS
- Active front ends

Description

1200 V, 11 mΩ silicon-carbide MOSFET t-type three-level module in a 62.8 × 56.7 mm baseplate-less housing.

Key specifications

Parameter	Value
V_{DSS}	1200 V
$R_{DS(on)}$ typ., T_{vj} = 25 °C	11 mΩ
I_D nominal	100 A
Topology	T-type three-level
T_{vj} op. max	175 °C
Outline	62.8 × 56.7 mm, baseplate-less, press-fit pins

Full characterization data

Thermal resistance, switching energies and times, capacitances, gate charge and typical characteristic curves for IHSM12R011T2 are available on request: request the full data or write to sales@ironhawksemi.com.

© 2026 IRONHAWK · Specifications are subject to change without notice

Package

Press-fit low-profile, large. Mechanical outline drawing, STEP model and PCB footprint available on request.

Ordering information

Part number	Packing	MOQ	Lead time
IHSM12R011T2	Box	On request	On request

Information in this document is believed to be accurate but is subject to change without notice. Typical values are not guaranteed. The customer is responsible for validating suitability in the end application. IRONHAWK · sales@ironhawksemi.com

© 2026 IRONHAWK · Specifications are subject to change without notice